

Cranab FC53



Cranab FC53

Cranab FC53 is the crane of choice for small forwarders or large forestry wagons. It is also well-suited for direct mounting on large agricultural tractors.

Both its appearance and operating characteristics have a strong resemblance to the larger cranes in the Cranab family. The positive characteristics of the larger cranes can also be found on the FC53. Uncompromising design in combination with Cranab's production quality give FC53 the best possible footing.

The crane has been design using the highest quality materials, well-dimensioned bearing seatings and cylinders developed for intensive work.



Protected hose routing and high quality hoses ensure little downtime and trouble free operations.

A slewing motor with double gear racks gives exact positioning as well as a long life.

To obtain the best performance requires the valve to be matched to the crane's different functions.

We will always help you find the optimum valve solution from both cost-effectiveness and operational standpoints.

Cranab FC53 is a crane designed for those seeking a fast, small crane with the characteristics of a large crane.

Range of movement.	Technical data Telescopic:	Technical data Double Telescopic:																		
 <p>White area: the crane's range of movement.</p>	<p>Max. reach 6.5 m</p> <p>Lifting force at tip of boom:</p> <table> <tr> <td>at reach</td><td>3,0 m</td><td>1275 kg</td></tr> <tr> <td></td><td>5,0 m</td><td>835 kg</td></tr> <tr> <td></td><td>6,5 m</td><td>632 kg</td></tr> </table> <p>Lifting torque, gross 53 kNm</p> <p>Slewing torque, gross 12 kNm</p> <p>Slewing angle 380°</p> <p>Boom extension 1,55 m</p> <p>Working pressure 18,5 MPa</p> <p>Recommended oil flow 40-80 l/min</p> <p>Weight with lowest pillar height 720 kg</p>	at reach	3,0 m	1275 kg		5,0 m	835 kg		6,5 m	632 kg	<p>Max. reach 8.5 m</p> <p>Lifting force at tip of boom:</p> <table> <tr> <td>at reach</td><td>3,0 m</td><td>1080 kg</td></tr> <tr> <td></td><td>5,3 m</td><td>775 kg</td></tr> <tr> <td></td><td>8,5 m</td><td>418 kg</td></tr> </table> <p>Lifting torque, gross 53 kNm</p> <p>Slewing torque, gross 12 kNm</p> <p>Slewing angle 380°</p> <p>Boom extension 3.21 m</p> <p>Working pressure 18,5 MPa</p> <p>Recommended oil flow 40-80 l/min</p> <p>Weight with lowest pillar height 870 kg</p>	at reach	3,0 m	1080 kg		5,3 m	775 kg		8,5 m	418 kg
at reach	3,0 m	1275 kg																		
	5,0 m	835 kg																		
	6,5 m	632 kg																		
at reach	3,0 m	1080 kg																		
	5,3 m	775 kg																		
	8,5 m	418 kg																		
<p>Size</p>  <p>Suitable for large agricultural tractors/small forwarders</p>																				

Right to alteration reserved. The pictures do not always show cranes in standardversion.